	HEALTH FLAMMABILITY PHYSICAL PPE	1 0 1 B	Flammability Instability Health Special Hazard	Printed: 03/23/2012 Revision: 12/14/2011
1. Pro	oduct and (Compa	ny Identification	
Product Code:	00013			
Product Name:	GrimeFyter			
Manufacturer Information				
Company Name:	Skyrex Inc.			
	109 Aldene Ro	ad		
	Roselle, NJ 07	7203		
Emergency Contact:	ChemTel		(800)255-3924	
Intended Use:	Cab Cleaner			
2. Hazards Identification				
GHS Classification				
GHS Classification	Placard	Key word	GHS Hazard	
Serious Eye Damage/Eye Irritation, Category 2B	v none	Warning	Causes eye irritation	

Skin Corrosion/Irritation, Category 3 Warning Causes mild skin irritation none

GHS Hazard Phrases

H320 - Causes eye irritation. H316 - Causes mild skin irritation.

GHS Precaution Phrases

P264 - Wash hands thoroughly after handling.

GHS Response Phrases

P305+351+338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+313 - If eye irritation persists, get medical advice/attention. P332+313 - If skin irritation occurs, get medical advice/attention.

GHS Storage and Disposal Phrases

Potential Health Effects (Acute and Chronic)

Causes eye irritation. Causes redness and pain.

Skin: Causes skin irritation. A skin notation is not recommended by ACGIH, based on estimates from physiologically based pharmacokinetic models which indicate that, even in worst-case dermal-exposure scenarios, 2-butoxyethanol is not absorbed in amounts sufficient to cause red blood cell hemolysis in humans.

Ingestion: May cause irritation of the digestive tract. May cause gastrointestinal irritation with nausea, vomiting and diarrhea.

Inhalation: May cause central nervous system effects such as nausea and headache.

LD 50 / LC 50

Ingredient CAS# 497-19-8, Sodium carbonate: CAS# 497-19-8: Draize test, rabbit, eye: 100 mg/24H Moderate; Draize test, rabbit, eye: 50 mg Severe; Draize test, rabbit, skin: 500 mg/24H Mild;

Page:

1

Inhalation, Mouse: $LC50 = \{>91 \text{ mg/m3}\}$ Inhalation, rat: LC50 = 2300 mg/m3/2H;. Oral, mouse: LD50 = 6600 mg/kg; Oral, Mouse: $LD50 = \{250 \text{ mg/kg}\}$. Oral, Rat: $LD50 = \{640\}$

Ingredient CAS# 527-07-1, Sodium Gluconate: Not available.

Ingredient CAS# 194491-31-1, EDTA, tetrasodium salt, hydrate: CAS# 139-13-9: Oral, Mouse: LD50 = 3160 mg/kg;. Oral, Rat: LD50 = 1100 mg/kg CAS# 64-02-8: Draize test, rabbit, eye: 1900 ug; Draize test, rabbit, skin: 500 mg/24H Moderate;

Ingredient CAS# 111-76-2, Ethanol, 2-Butoxy-: CAS# 111-76-2: Dermal, guinea pig: LD50 = 230 uL/kg; Draize test, rabbit, eye: 100 mg Severe; Inhalation, Mouse: LC50 = 700 ppm/7H Inhalation, rat: LC50 = 450 ppm/4H. Oral, mouse: LD50 = 1230 mg/kg; Oral, mouse: LD50 = 1167 mg/kg; Oral, Rabbit: LD50 = 300 mg/kg; Oral, Rabbit: LD50 = 320 mg/kg; Oral, rat: LD50 = 470 mg/kg; Oral, rat: LD50 = 917 mg/kg; Skin, Rabbit: LD50 = 220 Humans are less susceptible than

Skin, Rabbit: LD50 = 220 Humans are less susceptible than rodents to 2-butoxyethanol 2-Butoxyethanol gives toxic results when tested on rabbits and rats. It does not behave the same when humans are exposed to it. This is explained by the different makeup of the red blood cells of test animals vs. humans. Test animal red blood cells are hypersensitive to 2-butoxyethanol when compared to humans.

	3. Composition/Information on Ingredients				
Hazardous Components (Chemical Name) CAS # Concentration					
1.	Sodium silicate	13870-28-5	<5.0 %		
2.	Sodium carbonate	497-19-8	<5.0 %		
3.	Sodium Gluconate	527-07-1	<5.0 %		
4.	EDTA, tetrasodium salt, hydrate	194491-31-1	<5.0 %		
5.	Alcohol ethoxylate	68439-46-3	5.0 - 10 %		
6.	Ethanol, 2-Butoxy-	111-76-2	5.0 - 10 %		
	4. First Aid Measures				

Emergency and First Aid Procedures

Eyes: Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids.

Skin: Flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse.

Ingestion: Call a poison control center. Do not use mouth-to-mouth resuscitation if victim ingested or inhaled the substance; induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.

Inhalation: Remove from exposure and move to fresh air immediately.

Note to Physician

Treat symptomatically and supportively.

Signs and Symptoms Of Exposure

5. Fire Fighting Measures					
Flash Pt:	NA Method Used: Estimate				
Explosive Limits:	LEL:	UEL:			
Autoignition Pt:	NA				

Fire Fighting Instructions

As in any fire, wear a self-contained breathing apparatus in pressure-demand, MSHA/NIOSH (approved or equivalent), and full protective gear. During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion. Runoff from fire control or dilution water may cause pollution. Dusts at sufficient concentrations can form explosive mixtures with air. Will burn if involved in a fire. Combustible liquid and vapor.

Flammable Properties and Hazards

Suitable Extinguishing Media

Substance is noncombustible; use agent most appropriate to extinguish surrounding fire. Use agent most appropriate to extinguish fire. For small fires, use water spray, dry chemical, carbon dioxide or chemical foam.

Unsuitable Extinguishing Media

6. Accidental Release Measures

Steps To Be Taken In Case Material Is Released Or Spilled

Use proper personal protective equipment as indicated in Section 8.

Spills/Leaks: Vacuum or sweep up material and place into a suitable disposal container. Wear a self contained breathing apparatus and appropriate personal protection. (See Exposure Controls, Personal Protection section). Avoid generating dusty conditions. Provide ventilation. Do not let this chemical enter the environment. Clean up spills immediately, observing precautions in the Protective Equipment section. Sweep up, then place into a suitable container for disposal. Absorb spill with inert material (e.g. vermiculite, sand or earth), then place in suitable container. Remove all sources of ignition. Use a spark-proof tool.

7. Handling and Storage

Precautions To Be Taken in Handling

Do not get in eyes, on skin, or on clothing. Do not ingest or inhale. Wash thoroughly after handling. Use with adequate ventilation. Avoid ingestion and inhalation. Remove contaminated clothing and wash before reuse. Keep container tightly closed.

Precautions To Be Taken in Storing

Store in a cool, dry place. Store in a tightly closed container. Store in a cool, dry, well-ventilated area away from incompatible substances. Aqueous solutions cannot be stored in aluminum, carbon steel, copper, copper alloys, zinc or nickel containers.

8. Exposure Controls/Personal Protection					
Hazardous Components (Chemical Name)	CAS #	OSHA PEL	ACGIH TLV	Other Limits	
1. Sodium silicate	13870-28-5	i			
2. Sodium carbonate	497-19-8	5			

На	zardous Components (Chemical Name)	CAS#	OSHA PEL	ACGIH TLV	Other Limits
3.	Sodium Gluconate	527-07-1			
4.	EDTA, tetrasodium salt, hydrate	194491-31-1			
5.	Alcohol ethoxylate	68439-46-3			
6.	Ethanol, 2-Butoxy-	111-76-2	50 ppm	20 ppm	

Respiratory Equipment (Specify Type)

A respiratory protection program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements or European Standard EN 149 must be followed whenever workplace conditions warrant respirator use. Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Eye Protection

Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.

Protective Gloves

Wear appropriate protective gloves to prevent skin exposure.

Other Protective Clothing

Wear appropriate protective clothing to prevent skin exposure.

Engineering Controls (Ventilation etc.)

Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Use only under a chemical fume hood. Use adequate ventilation to keep airborne concentrations low.

Work/Hygienic/Maintenance Practices

9. Physical and Chemical Properties			
Physical States:	[]Gas [X]Liquid []Solid		
Freezing Point:	< 0 C		
Boiling Point:	> 100 C		
Decomposition Temperature:	NE		
Autoignition Pt:	NA		
Flash Pt:	NA Method Used: Estimate		
Specific Gravity (Water = 1):	~ 1.04		
Vapor Pressure (vs. Air or mm Hg):			
Vapor Density (vs. Air = 1):			
Evaporation Rate:	1 (H2O=1)		
Solubility in Water:	misc.		
Percent Volatile:	~ 90 % by weight.		
pH:	~ 12.5		
Appearance and Odor Appearance: green. Liquid. Odor: alcohol-like.			
	10. Stability and Reactivity		
Stability:	Unstable [] Stable [X]		
Conditions To Avoid - Instability			

Incompatibility - Materials To Avoid

acids, fluorine, Hydrogen peroxide, phosphorus pentoxide, 6-trinitrotoluene.

Hazardous Decomposition Or Byproducts

Carbon monoxide, Carbon dioxide, irritating and toxic fumes and gases, sodium oxide. Nitrogen oxides.

Possibility of Hazardous Reactions: Will occur [] Will not occur [X]

Conditions To Avoid - Hazardous Reactions

11. Toxicological Information

Toxicological Information

Epidemiology: No information found.

Teratogenicity: Teratogenic effects have occurred in experimental animals.

Reproductive Effects: Mutagenicity: Neurotoxicity: Other Studies: Teratogenicity: No information available. No information available.

Teratogenicity: EDTA and its sodium salts have been reported to cause birth defects in lab animals only at exaggerated doses that were toxic to the mother. These effects are likely associated with zinc deficiency due to chelation. Exposures having no effects on the mother should have no effects on the fetus. Effects on Fertility: Post-implantation mortality (e.g., dead and/or resorbed implants per total number of implants). Oral, rat: TDLo = 7632mg/kg Cytogenetic Analysis: intraperitoneal-mouse = $\{50 \text{ mmol/L}\}$. DNA Inhibition: hamster fibroblast 500ug/L, rabbit kidney 250umol/L.

Carcinogenicity/Other Information

CAS# 497-19-8: Not listed by ACGIH, IARC, NTP, or CA Prop 65. CAS# 527-07-1: Not listed by ACGIH, IARC, NTP, or CA Prop 65. CAS# 194491-31-1: Not listed by ACGIH, IARC, NTP, or CA Prop 65. CAS# 139-13-9: ACGIH: Not listed.

California: carcinogen, initial date 1/1/88. NTP: Suspect carcinogen.

CAS# 111-76-2: ACGIH: A3 - Confirmed animal carcinogen with unknown relevance to humans.

California: Not listed.

NTP: Not listed.

IARC: Not listed.

На	zardous Components (Chemical Name)	CAS #	NTP	IARC	ACGIH	OSHA
1.	Sodium silicate	13870-28-5				
2.	Sodium carbonate	497-19-8				
3.	Sodium Gluconate	527-07-1				
4.	EDTA, tetrasodium salt, hydrate	194491-31-1				
5.	Alcohol ethoxylate	68439-46-3				
6.	Ethanol, 2-Butoxy-	111-76-2		3	A3	

12. Ecological Information

General Ecological Information

Ecotoxicity: Fish: Bluegill/Sunfish: LC50 = 320 mg/L; 96 hr. Static Conditions No data available.

Environmental: No information available.

Physical: No information available.

Other: Do not empty into drains. No data available. Catfish (tap water) 129 ppm/96H.

Biological Oxygen Demand (BOD): 1%, 5 days.

Physical: No bioconcentration is expected because of the relatively high water solubility.

Other: None. 24-Hr. LC50; goldfish: 1650 mg/L 96-Hr. LC50; bluegill sunfish: 1490 mg/L96-Hr. LC50; tidewater silversides: 1250 mg/L

TERRESTRIAL FATE: Based on a recommended classification scheme, an estimated Koc value of 67,, determined from an experimental log Kow and a recommended regression-derived equation, indicates that

ethylene glycol mono-n-butyl ether is expected to have high mobility in soil. An estimated BCF value of 2.5 was calculated for ethylene glycol mono-n-butyl ether, using an experimental log Kow of 0.83 and a recommended regression-derived equation. According to a recommended classification scheme, this BCF value suggests that bioconcentration in aquatic organisms is low.

Physical: No information found.

Other: An estimated BCF value of 2.5,, from an experimental log Kow, suggests that ethylene glycol mono-n-butyl ether bioconcentration in aquatic organisms will be low, according to a recommended classification scheme.

13. Disposal Considerations

Waste Disposal Method

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. US EPA guidelines for the classification determination are listed in 40 CFR Parts 261. Additionally, waste generators must consult state and local hazardous waste regulations to ensure complete and accurate classification. RCRA P-Series: None listed.

RCRA U-Series: None listed.

14. Transport Information

Globally Harmonized System of Classification and Labelling

Serious Eye Damage/Eye Irritation, Category 2B - Warning! Causes eye irritation Skin Corrosion/Irritation, Category 3 - Warning! Causes mild skin irritation

LAND TRANSPORT (US DOT)

DOT Proper Shipping Name	NOT REGULATED FOR DOMESTIC TRANSPORT.
Packing Group:	III

LAND TRANSPORT (Canadian TDG)

TDG Shipping Name

Not Regulated. No information available.

15. Regulatory Information

US EPA SARA Title III

Hazardous Components (Chemical Name)	CAS #	Sec.302 (EHS)	Sec.304 RQ	Sec.313 (TRI)	Sec.110
1. Sodium silicate	13870-28-5	No	No	No	No
2. Sodium carbonate	497-19-8	No	No	No	No
3. Sodium Gluconate	527-07-1	No	No	No	No
4. EDTA, tetrasodium salt, hydrate	194491-31-1	No	No	No	No
5. Alcohol ethoxylate	68439-46-3	No	No	No	No
6. Ethanol, 2-Butoxy-	111-76-2	No	No	Yes-Cat. N230	No
Other US EPA or State Lists					
Hazardous Components (Chemical Name)	CAS #	CAA HAP,ODC	CWA NPDES	TSCA	CA PROP.65
1. Sodium silicate	13870-28-5	No	No	Inventory	No
2. Sodium carbonate	497-19-8	No	No	Inventory	No
3. Sodium Gluconate	527-07-1	No	No	Inventory	No
4. EDTA, tetrasodium salt, hydrate	194491-31-1	No	No	No	No
5. Alcohol ethoxylate	68439-46-3	No	No	Inventory	No
6. Ethanol, 2-Butoxy-	111-76-2	No	No	Inventory	No
Hazardous Components (Chemical Name)	CAS #	CA TAC, Title 8	MA Oil/HazMat	MI CMR, Part 5	NC TAP
1. Sodium silicate	13870-28-5	No	No	No	No
2. Sodium carbonate	497-19-8	No	No	No	No
3. Sodium Gluconate	527-07-1	No	No	No	No

Hazardous Components (Chemical Name)	CAS #	CA TAC, Title 8	MA Oil/HazMat	MI CMR, Part 5	NC TAP
4. EDTA, tetrasodium salt, hydrate	194491-31-1	No	No	No	No
5. Alcohol ethoxylate	68439-46-3	No	No	No	No
6. Ethanol, 2-Butoxy-	111-76-2	TAC, Title 8	Yes	Part 5	No
Hazardous Components (Chemical Name)	CAS #	NJ EHS	NY Part 597	PA HSL	SC TAP
1. Sodium silicate	13870-28-5	No	No	No	No
2. Sodium carbonate	497-19-8		No	No	No
3. Sodium Gluconate	527-07-1		No	No	No
 EDTA, tetrasodium salt, hydrate Alcohol ethoxylate 	194491-31-1 68439-46-3		No No	No No	No No
 Alcohol ethoxylate Ethanol, 2-Butoxy- 		Yes - 0275	No	Yes - 1	Yes - Cat.
Hazardous Components (Chemical Name)	CAS#	WI Air			100 000
1. Sodium silicate	13870-28-5				
2. Sodium carbonate	497-19-8	No			
3. Sodium Gluconate	527-07-1	No			
4. EDTA, tetrasodium salt, hydrate	194491-31-1	No			
5. Alcohol ethoxylate	68439-46-3				
6. Ethanol, 2-Butoxy-	111-76-2	Yes			
SARA (Superfund Amendments and					
Reauthorization Act of 1986) Lists:					
Sec.302:	EPA SARA Title III Section 302 Extremely Hazardous Chemical with TPQ. * indicates 10000 LB TPQ if not volatile.				
Sec.304:	EPA SARA Title III Section 304: CERCLA Reportable + Sec.302 with Reportable Quantity. ** indicates statutory RQ.				
Sec.313:	EPA SARA Title III Section 313 Toxic Release Inventory. Note: -Cat indicates a member of a chemical category.				
Sec.110:	EPA SARA 110 Superfund Site Priority Contaminant List				
TSCA (Toxic Substances Control Act) Lists:					
Inventory:	Chemical Listed i	in the TSCA Invento	ory.		
5A(2):	Chemical Subject	to Significant New I	Rules (SNURS)		
6A:	Commercial Chen	nical Control Rules			
8A:	Toxic Substances	Subject To Informa	tion Rules on Produc	tion	
8A CAIR:	Comprehensive A	Assessment Informat	ion Rules - (CAIR)		
8A PAIR:	Preliminary Asses	ssment Information	Rules - (PAIR)		
8C:	Records of Allega	tions of Significant	Adverse Reactions		
8D:	Health and Safety	Data Reporting Rul	les		
8D TERM:	Health and Safety	Data Reporting Ru	le Terminations		
12(b):	Notice of Export				
Other Important Lists:					
CWA NPDES:	EPA Clean Water Act NPDES Permit Chemical				
CAA HAP:	EPA Clean Air A	ct Hazardous Air Po	ollutant		
CAA ODC:	EPA Clean Air A	ct Ozone Depleting	Chemical (1=CFC, 2	=HCFC)	

California Proposition 65

CA TAC:	California AB 1807 - Toxic Air Contaminants
CA Title 8:	California Hazardous Substances List: Title 8, Sec. 339
MI CMR:	Michigan Critica Materials Register
MI Part 5:	Michigan DEQ WRP Part 5 Pollutants List
NC TAP:	North Carolina Toxic Air Pollutants
NJ EHS:	New Jersey Environmental Hazardous Substances List
NY Part 597:	New York Part 597 List of Hazardous Substances
PA HSL:	Pennsylvania Hazardous Substances List
SC TAP:	South Carolina Toxic Air Pollutants
WI Air:	Wisconsin Reportable Air Contaminants

International Regulatory Lists:

EPA Hazard Categories:

This material meets the EPA 'Hazard Categories' defined for SARA Title III Sections 311/312 as indicated:

[] Yes [X] No	Acute (immediate) Health Hazard
[] Yes [X] No	Chronic (delayed) Health Hazard
[] Yes [X] No	Fire Hazard
[] Yes [X] No	Sudden Release of Pressure Hazard
[] Yes [X] No	Reactive Hazard

16. Other Information

Company Policy or Disclaimer

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution.

Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

*NOTE: Hazard Determination System (HDS) rating are based on a 0-4 scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although these ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HDS ratings are to be used with a fully implemented program to relay the meanings of this scale.